GRS-7022-2403E

# **OG GREASE 500**

### LUBRICANT FOR WIRE ROPES

**OG GREASE 500** is a solvent-diluting lubricant for open gears and wire ropes. It can be applied by brushing because tacky lubricant is diluted with a solvent providing high permeability, and creates a strong coating after the solvent has evaporated.

#### SPECIAL FEATURES

#### 1. Easy to apply

**OG GREASE 500** can be applied by brushing without heating because tacky lubricant is diluted with a solvent.

## 2. Excellent load-carrying and anti-wear properties

**OG GREASE 500** is highly resistant to shock load because of its extraordinary strong tacky film after the solvent has evaporated. It prevents wear by protecting friction components.

## 3. Excellent rust and corrosion preventive properties

**OG GREASE 500** is not easily washed off when sprayed with water. Therefore, gears and wire ropes are ensured extended life because it prevents rust formation and surface corrosion.

#### APPLICATIONS

**OG GREASE 500** is recommended for use in open gears and wire ropes.

#### CONTAINER

16-kg can

### TYPICAL PROPERTIES OF OG GREASE 500

Appearance, Color		Semi Liquid, Black
Viscosity(50°C)	$mm^2/s$	470
Flash Point (Setaflash Closed Cup Test)	°C	65
Copper Strip Corrosion Temp., 24h)	(Room	No color change to green or black

Note: The typical properties may be changed without notice. (July 2017)



## Handling Precautions

### lacksquare Follow these precautions when handling this product.

Composition:	Base Oil(s):Highly refined mineral oil, Hydrocarbons(<2% aromatics), Additives	
Hazard pictograms:	<u>(1)</u>	
Signal word:	Warning	
Hazard Statement:	Combustible liquid	
	May cause respiratory irritation, or May cause drowsiness or dizziness.	
	Harmful to aquatic life	
	Harmful to aquatic life with long lasting effects.	
Precautionary Statements:	Do not handle until all safety precautions have been read and understood.	
Prevention	Wear protective gloves/protective clothing/eye protection/face protection.	
	• Do not allow the eyes to become exposed to the product. Do not swallow the product.	
	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
	Avoid release to the environment.	
	Use only outdoors or in a well-ventilated area.	
	Avoid breathing dust/fume/gas/mist/vapours/spray.	
	Wash hands thoroughly after handling.	
	• Do not eat, drink or smoke when using this product.	
Response	• IF SWALLOWED: Immediately call a POISON CENTER/doctor.	
	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.	
	• If the eyes are exposed to the product: Rinse the eyes with plenty of running water and	
	immediately contact a physician.	
	• IF ON SKIN: Wash with plenty of soap and water.	
	• IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
Storage	The product must be stored in a cool, well-ventilated location where it will not be exposed	
	to direct sunlight.	
	Containers that have been opened must be tightly sealed.	
	Store in a well-ventilated place. Keep container tightly closed.	
	Store locked up.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international	
	regulations.	
	If there are any doubts about proper methods of handling the product, contact the point of	
	purchase before proceeding with usage.	