

AUT-0063-2402E



1-1-2 Otemachi, Chiyoda-ku, Tokyo 100-8162, Japan

GEAR GRAND GL-5 80W-90

Gear oil for large vehicles such as buses and trucks with manual transmission and differential gears

GEAR GRAND GL-5 80W-90 is an automotive gear oil made from highly refined base oil and topperformance extreme-pressure agents, metal anticorrosion agents, detergent-dispersants and other additives. It meets the API service classification grade GL-5.

Special Features

1. Automotive Gear Oil for Combined Use

The oil properties required for transmission gear and differential gear are different. For transmission oil, general properties as gear oil and also synchronizing characteristics which relates to shift operability and copper (part material) protective property are required. And for differential oil, anti-wear and extreme pressure properties are important under severe load conditions.

GEAR GRAND GL-5 80W-90 satisfies the properties demanded for both applications and can unify two kinds of oils to one. In addition, it can simplify the inventory control and decrease the risk of false filling.

2. Fuel Saving Effect

GEAR GRAND GL-5 80W-90 is oil of 80W-90 viscosity grade and indicates fuel saving effect because it reduces stirring resistance compared with single grade 90, and gives smooth shift operability at low temperature.

3. Outstanding Lubrication Performance

GEAR GRAND GL-5 80W-90 contains optimized additives especially sulfur-phosphorus extreme-pressure agent and provides excellent lubrication performance. The load carrying capacity of this oil meets the API service classification grade GL-5.

Applications

Transmission and differential gears of large size vehicles (applicable to resin type synchronizer ring as well as brass)

Containers

200-liter drum, 20-liter can

•Typical Properties of GEAR GRAND GL-5 80W-90

API Service Grade			GL-5
SAE Viscosity Grade			80W-90
Color	(ASTM)		L2.0
Density	(15°C)	g/cm ³	0.896
Viscosity	(40°C)	mm ² /s	144.5
	(100°C)	mm ² /s	15.67
Viscosity Index			112
Flash Point	(COC)	°C	234
Pour Point		°C	-32.5
Acid Number		mgKOH/g	1.33

Note: The typical properties may be changed without notice. (August 2023)



Handling Precautions

Composition :	Base Oil(s), Additives		
Hazard pictograms:			
Signal word:	Warning		
Hazard Statement:	May cause an allergic skin reaction.		
Precautionary Statements:	• Do not handle until all safety precautions have been read and understood.		
Prevention	• Wear protective gloves/protective clothing/eye protection/face protection.		
	• Do not allow the eyes to become exposed to the product. Do not swallow the product.		
	Contaminated work clothing should not be allowed out of the workplace.		
	Avoid breathing dust/fume/gas/mist/vapours/spray.		
	• Wash hands thoroughly after handling.		
	• Do not eat, drink or smoke when using this product.		
Response	• IF SWALLOWED: Immediately call a POISON CENTER/doctor.		
	• IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.		
	• If the eyes are exposed to the product: Rinse the eyes with plenty of running water and		
	immediately contact a physician.		
	• IF ON SKIN: Wash with plenty of soap and water.		
	• If skin irritation or a rash occurs: Get medical advice/attention.		
	• Take off contaminated clothing and wash it before reuse.		
Storage	• The product must be stored in a cool, well-ventilated location where it will not be exposed		
	to direct sunlight.		
	• Containers that have been opened must be tightly sealed.		
Disposal	Dispose of contents/container in accordance with local/regional/national/international		
	regulations.		
	• If there are any doubts about proper methods of handling the product, contact the point of		
	purchase before proceeding with usage.		