

GRS-7002-2403E

EPNOC GREASE 203K 2

Multipurpose Grease for Very Low Temperatures

In recent years, machines used in refrigerators and freezers have been exposed to much lower temperatures than ever before. When grease is used in such cold environments, it can harden, exert heavy loads on the machine, prevents the machinery from moving, and even damage the equipment. **EPNOC GREASE 203K 2** is a grease blended with lithium soap thickener, an ester-type synthetic base oil, and extreme-pressure agents and other additives, it can be used at very low temperatures (-70 °C).

● SPECIAL FEATURES

1. Usable at Very Low Temperature (-70°C)

The pour point of paraffin-type mineral oils, which are commonly used as the base oils of grease, is around -15°C, so such greases become hard below that temperature. Since **EPNOC GREASE 203K 2** uses an ester-type synthetic base oil with an extremely low pour point, it provides outstanding performances at temperatures as low as -70 °C (203 Kelvin).

2. Able to Withstand Heavy Loads

Since **EPNOC GREASE 203K 2** contains extreme-pressure additives, it has a high Timken value and can withstand very heavy loads.

3. Excellent Shear Stability

When a grease with poor mechanical shear stability is exposed to mechanical shear in bearings or other applications, the fiber structure of the grease's thickener is broken, resulting in softening and oil separation. Thanks to its excellent mechanical shear stability, these problems do not occur with **EPNOC GREASE 203K 2**.

4. Outstanding Oxidation Stability

EPNOC GREASE 203K 2 has outstanding oxidation stability, so the grease will not degrade or undergo oil separation due to oxidation during storage or use. As a result, **EPNOC GREASE 203K 2** can be used for long periods of time.

● APPLICATIONS

- (1) Machines used in refrigerators and freezers
- (2) Snow-removal machines
- (3) Snowmobiles
- (4) Ski lifts

● CONTAINERS

16 kg pail can

● TYPICAL PROPERTIES OF EPNOC GREASE 203K 2

Thickener		lithium soap
Base oils		ester-type synthetic oil
Type		
Kinematic viscosity (40°C)	mm ² /s	13.9
Kinematic viscosity (100°C)	mm ² /s	3.41
Viscosity index		123
Penetration (60 strokes)		276
(100,000 strokes)		341
Dropping point	°C	182
Oil separation (100 °C, 24h)	mass%	1.0
Water washout (38 °C, 1h)	mass%	2.0
Oxidation stability (99°C, 100h)	kPa	35
Copper strip corrosion (100°C, 24h)		No change to green or black
Timken test OK load	kg	20.43
Low-temperature torque (-40 °C)		
Starting torque/rotating torque	N·m	0.16/0.04
Approx. operating temperature range	°C	-70 to 120

Note: The typical properties are subject to change without notice. (March 2024)



Handling Precautions

▼ Follow these precautions when handling this product.

Composition :	Base Oil(s), Thickener, Additives
Hazard pictograms:	
Signal word:	Warning
Hazard Statement:	May cause an allergic skin reaction May cause damage to organs (blood systems) Harmful to aquatic life Harmful to aquatic life with long lasting effects
Precautionary Statements:	<ul style="list-style-type: none">• Do not handle until all safety precautions have been read and understood.• Wear protective gloves/protective clothing/eye protection/face protection.• Do not allow the eyes to become exposed to the product. Do not swallow the product.• Avoid release to the environment.• Contaminated work clothing should not be allowed out of the workplace.• Do not breathe dust/fume/gas/mist/vapours/spray.• Wash hands thoroughly after handling.• Do not eat, drink or smoke when using this product.
Response	<ul style="list-style-type: none">• IF SWALLOWED: Immediately call a POISON CENTER/doctor.• IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.• If the eyes are exposed to the product: Rinse the eyes with plenty of running water and immediately contact a physician.• IF ON SKIN: Wash with plenty of soap and water.• If skin irritation or a rash occurs: Get medical advice/attention.• Take off contaminated clothing and wash it before reuse
Storage	<ul style="list-style-type: none">• The product must be stored in a cool, well-ventilated location where it will not be exposed to direct sunlight.• Containers that have been opened must be tightly sealed.• Store locked up.
Disposal	<ul style="list-style-type: none">• Dispose of contents/container in accordance with local/regional/national/international regulations.• If there are any doubts about proper methods of handling the product, contact the point of purchase before proceeding with usage.