IND-2514-2503E

POWER FLUSH

Cleaning agent for oil flushing

Sediment of degraded oil and external contaminants are often accumulated in piping such as hydraulic equipment and turbine equipment that have been used for a long time. If these are not sufficiently removed during oil change, malfunction of the valve or clogged filter may occur. **POWER FLUSH** is a flushing aid developed to allow more efficient work when you flush the inside of piping such as hydraulic equipment and turbine equipment.

SPECIAL FEATURES

Excellent flushing effect

POWER FLUSH enhances the flushing effect because it has a high ability to dissolve and disperse sediment of degraded oil and other organic substances accumulated in piping.

APPLICATIONS

Add **POWER FLUSH** to flushing oil during oil flushing.

• HOW TO USE POWER FLUSH

- (1) The best method is to add 1% of **POWER FLUSH** to the amount of oil used for flushing and circulate for about 1 to 2 months.
- (2) The method of adding **POWER FLUSH** to the equipment during operation is also effective, where one to two months before the oil change is scheduled.
- (3) Adding a large amount (2% or more) of **POWER FLUSH** or using it for more than two months does not change the effect.
- (4) If the inside of the piping is dirty, **POWER FLUSH** will dissolve the dirt, so the color of the flushing oil containing **POWER FLUSH** will normally be dark brown.
- (5) In order to clean the inside of the facilities more, we recommend to flush with fresh oil again after flushing work using **POWER FLUSH**.

CAUTION (About the remaining POWER FLUSH)

Since **POWER FLUSH** does not chemically react with various additives used for mineral oil type hydraulic fluid and turbine oil, there is no practical problem even if it remains a little in the equipment.

However, if it remains in large quantities, the properties of the new oil after flushing may change, so it is important to minimize remaining oil as much as possible.

CONTAINERS

20-liter can

TYPICAL PROPERTIES OF POWER FLUSH

Appearance			Light yellow, Liquid
Color (ASTM)			L0.5
Density	(15°C)	g/cm ³	0.849
Kinematic viscosity	(40 °C)	mm^2/s	50.6
Flash point	(PM)	°C	67
Pour point		°C	-12.5
Acid number		mgKOH/g	0.03

Note: The typical properties may be changed without notice. (February 2025)

Handling **Precautions**

lacktriangledown Follow these precautions when handling this product.

	<u></u>	
Composition:	Mixtures(Additives, Heavy Petroleum Naphtha)	
Hazard pictograms:	<u>(1)</u>	
Signal word:	Warning	
Hazard Statement:	Combustible liquid	
	Causes skin irritation	
	Harmful to aquatic life	
	Harmful to aquatic life with long lasting effects	
Precautionary Statements:	• Do not handle until all safety precautions have been read and understood.	
Prevention	Wear protective gloves/protective clothing/eye protection/face protection.	
	• Do not allow the eyes to become exposed to the product. Do not swallow the product.	
	• Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
	Avoid release to the environment.	
	Wash hands thoroughly after handling.	
	• Do not eat, drink or smoke when using this product.	
Response	• IF SWALLOWED: Immediately call a POISON CENTER/doctor.	
	• IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.	
	• If the eyes are exposed to the product: Rinse the eyes with plenty of running water and	
	immediately contact a physician.	
	• IF ON SKIN: Wash with plenty of soap and water.	
	If skin irritation occurs: Get medical advice/attention.	
	• Take off contaminated clothing and wash it before reuse.	
Storage	• The product must be stored in a cool, well-ventilated location	
	where it will not be exposed to direct sunlight.	
	Containers that have been opened must be tightly sealed.	
	Store in a well ventilated place.	
Disposal	• Dispose of contents/container in accordance with local/regional/national/international	
	regulations.	
	· If there are any doubts about proper methods of handling the product, contact the point of	
	purchase before proceeding with usage.	