

ANTIRUST TERAMI SC

Barium-free solvent-diluting cleaning and temporary rust preventive oil

ANTIRUST TERAMI SC is Barium-free solvent-diluting cleaning and temporary rust preventive oil, which was developed through many years of research, and its superior performance has been proven in a wide range of applications. ANTIRUST TERAMI SC, which does not contain petrolatum, provides good working efficiency, good cleaning performance and high protection performance against corrosion and oil stain.

● SPECIAL FEATURES

1. Excellent Rust Prevention

ANTIRUST TERAMI SC delivers excellent protection from rust due to the most suitable mineral oil and additives.

2. Low Risk of Fire

ANTIRUST TERAMI SC has a high flash point although it contains solvents. So it can be used with low risk of fire.

3. Good Removal

ANTIRUST TERAMI SC can be easily removed by using a petroleum solvent or alkaline process cleaner.

4. Easy to Use

ANTIRUST TERAMI SC is not sticky because petrolatum is not contained and excellent in the working efficiency. Moreover, it is easy to pass through a filter. It is expected that quantity of application will be decreased.

● APPLICATIONS

For various processing parts and machine parts

■ STORAGE PRECAUTIONS

When ANTIRUST TERAMI SC is left in a cold place in winter etc., some of the additives might be separated very unusually. So, it should be kept indoors. When oil separation might occur, please stir well before using.

● COATING METHODS

Immersion, Spraying, Brushing

● CONTAINERS

200-liter drums and 20-liter cans

● Typical Properties of ANTIRUST TERAMI SC

Appearance			Light yellow liquid
Color	(ASTM)		L2.5
Density	(15°C)	g/cm ³	0.809
Flash point	(PM)	°C	85
Viscosity	(40°C)	mm ² /s	2.4
Water displacement	(JIS K2246)		No rust
Metal strip corrosion	(JIS K2246 NP-3)		Passed
Humidity cabinet test	(Class A holding time)	h	>720
Protection	(Indoors)	months	3
Type of film			Semi-dry and transparent film
Film thickness		μm	1.5

Note: The typical properties may be changed without notice. (June 2010).



Handling Precautions

▼ Follow these precautions when handling this product.

Composition :	Base Oil, Additives
Precautionary pictograms:	
Signal word:	Danger
Hazard Statement:	Combustible liquid May be fatal if swallowed and enters airways
Precautionary Statements:	<ul style="list-style-type: none">• Do not handle until all safety precautions have been read and understood.• Wear protective gloves/protective clothing/eye protection/face protection.• Do not allow the eyes to become exposed to the product. Do not swallow the product.• Keep away from heat/sparks/open flames/hot surfaces – No smoking.• Use explosion-proof electrical/ventilating/lighting/equipment.• Ground/bond container and receiving equipment.• Wash hands thoroughly after handling.• Do not eat, drink or smoke when using this product.
Response	<ul style="list-style-type: none">• IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.• IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.• If the eyes are exposed to the product: Rinse the eyes with plenty of running water and immediately contact a physician.• IF ON SKIN: Wash with plenty of soap and water.• Do NOT induce vomiting.• In case of fire: Use suitable extinguishing media for extinction.
Storage	<ul style="list-style-type: none">• The product must be stored in a cool, well-ventilated location where it will not be exposed to direct sunlight.• Containers that have been opened must be tightly sealed.• Store in a well ventilated place. Keep cool.• Store locked up.
Disposal	<ul style="list-style-type: none">• Dispose of contents/container in accordance with local/regional/national/international regulations.• If there are any doubts about proper methods of handling the product, contact the point of purchase before proceeding with usage.