IND-5522-2405E

ANTIRUST TERAMI SC

Barium-free Solvent-diluting Cleaning and Intermediate Rust Preventive Oil

ANTIRUST TERAMI SC is a barium-free solvent-diluting cleaning and intermediate rust preventive oil developed based on years of research and experience. ANTIRUST TERAMI SC offers excellent workability due to its low viscosity, providing superior rust prevention, oil stain resistance and cleaning performance. Many rust preventive oils contain barium-based rust inhibitors. However, there are concerns about the impact of certain barium compounds on human health, even though they differ from these compounds. As a result, some regions (countries and states) in Europe and the United States are moving to strengthen regulations on barium and barium compounds. Additionally, in export-oriented industries, there is a trend to voluntarily limit the use of barium-based rust preventive oils. ANTIRUST TERAMI SC offers rust prevention performance equivalent to conventional barium-based rust preventive oils, making it a reliable choice for cleaning and intermediate rust prevention of export parts and components. ANTIRUST TERAMI SC is classified as NP-3-2 under JIS (Japanese Industrial Standards) K 2246.

SPECIAL FEATURES

1. Excellent Rust Prevention

ANTIRUST TERAMI SC provides excellent rust prevention due to the carefully selected mineral oil and rust inhibitors.

2. High Flash Point

Although **ANTIRUST TERAMI SC** is a solvent-diluting rust preventive oil, it has a relatively high flash point.

3. Easy Removal Capability

The film of **ANTIRUST TERAMI SC** can be easily removed using organic solvents or alkaline cleaning solutions.

4. Excellent Workability

ANTIRUST TERAMI SC does not contain film-forming agents like wax, making it ideal for cleaning precision parts to remove contaminants and facilitating easy filtration. It is also suitable for efficient coating methods such as dipping and spraying, potentially reducing consumption.

5. Environmentally Friendly

ANTIRUST TERAMI SC does not contain barium-based additives, making it highly compatible with environmental standards.

APPLICATIONS

For various machine parts and precision components

CLEANING AND COATING METHOD

Immersion, Spraying, Brushing

CONTAINERS

200-liter drum and 20-liter pail can

STORAGE PRECAUTIONS

Whenever possible, store this oil indoors. If left in a cold place, such as during winter, some additives may occasionally precipitate and cause cloudiness. If cloudiness or separation occurs, stir the oil at room temperature before use.

● TYPICAL PROPERTIES OF ANTIRUST TERAMI SC

Appearance			Light yellow liquid
Color	(ASTM)		L3.0
Density	(15°C)	g/cm ³	0.816
Kinematic viscosity	(40°C)	mm^2/s	2.49
Flash point	(PM)	°C	80
Water displacement			Pass
Metal strip corrosion			Pass
Humidity cabinet test	(Class A holding time)	h	>720
Rust protection	(Indoors)	months	3
Type of coating			Semi-dry and transparent film
Film thickness		μm	1.5

Note: The typical properties may be changed without notice. (May 2024).



Handling Precautions

lacksquare Follow these precautions when handling this product.

Composition:	Base Oil(s), Additives		
Hazard pictograms:			
Signal word:	Danger		
Hazard Statement:	Combustible liquid		
	May be fatal if swallowed and enters airways		
	Harmful to aquatic life		
	Harmful to aquatic life with long lasting effects		
Precautionary Statements:	• Do not handle until all safety precautions have been read and understood.		
Prevention	Wear protective gloves/protective clothing/eye protection/face protection.		
	• Do not allow the eyes to become exposed to the product. Do not swallow the product.		
	· Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.		
	· Avoid release to the environment.		
	Wash hands thoroughly after handling.		
	• Do not eat, drink or smoke when using this product.		
Response	• IF SWALLOWED: Immediately call a POISON CENTER/doctor.		
	• IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.		
	• If the eyes are exposed to the product: Rinse the eyes with plenty of running water and		
	immediately contact a physician.		
	• IF ON SKIN: Wash with plenty of soap and water.		
	• Do NOT induce vomiting.		
Storage	• The product must be stored in a cool, well-ventilated location where it will not be exposed		
	to direct sunlight.		
	Containers that have been opened must be tightly sealed.		
	• Store in a well ventilated place.		
	Store locked up.		
Disposal	• Dispose of contents/container in accordance with local/regional/national/international		
	regulations.		
1	• If there are any doubts about proper methods of handling the product, contact the point of		
	purchase before proceeding with usage.		