IND-5518-2104E

ANTIRUST TERAMI LS

Barium-free long-term solvent-diluting rust preventive oil

ANTIRUST TERAMI LS was developed through many years of research, and its superior performance has been proven in a wide range of applications. **ANTIRUST TERAMI LS** is not sticky because petrolatum is not contained and excellent in the working efficiency.

SPECIAL FEATURES

1. Excellent Rust Prevention

ANTIRUST TERAMI LS is formulated with carefully selected mineral oil and rust-preventive additives. After the solvent has evaporated, ANTIRUST TERAMI LS forms a thin and non drying coating that provides excellent long-term protection from rust.

2. Low Risk of Fire

ANTIRUST TERAMI LS has a high flash point although it contains solvents. So it can be used with low risk of fire.

3. Good Removal

Film of **ANTIRUST TERAMI LS** is easily removed with a petroleum solvent or alkaline process cleaner.

4. Easy to Use

ANTIRUST TERAMI LS is not sticky because petrolatum is not contained and excellent in the working efficiency. Moreover, it is easy to pass through a filter. It is expected that quantity of application will be decreased.

5. Good for the Ecology

ANTIRUST TERAMI LS is an environmentally-friendly product due to barium-free type.

APPLICATIONS

Machine parts, precision machine parts, etc.

COATING METHOD

Immersion, spraying, brushing

CONTAINERS

200-liter drums and 20-liter cans

Typical Properties of ANTIRUST TERAMI LS

Appearance			Brown
Color	(ASTM)		L4.0
Density	(15°C)	g/cm ³	0.83
Viscosity	(40°C)	mm^2/s	5.0
Flash point	(PM)	°C	87
Water displacement	t (JIS K2246 6.29)		Pass
Metal strip corrosion	(JIS K2246	5 NP-3)	Pass
Humidity cabinet test	(Class A holding time)	h	> 1,200
Salt spray test	(Class A holding time)	h	> 48
Protection	(Indoors)	months	6
Type of film			Non
			drying
			and transpar-
			ent film
Film thickness	(Approx.)	μm	3

Note: The typical properties may be changed without notice. (June 2015).



Handling **Precautions**

lacksquare Follow these precautions when handling this product.

Composition:	Base Oil, Additives
Precautionary pictograms:	
Signal word:	Danger
Hazard Statement:	Combustible liquid
	May be fatal if swallowed and enters airways
Precautionary Statements:	• Do not handle until all safety precautions have been read and understood.
Prevention	• Wear protective gloves/protective clothing/eye protection/face protection.
	• Do not allow the eyes to become exposed to the product. Do not swallow the product.
	• Keep away from heat/sparks/open flames/hot surfaces – No smoking.
	Use explosion-proof electrical/ventilating/lighting/equipment.
	Ground/bond container and receiving equipment.
	Wash hands thoroughly after handling.
	• Do not eat, drink or smoke when using this product.
Response	• IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
	• IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
	• If the eyes are exposed to the product: Rinse the eyes with plenty of running water and
	immediately contact a physician.
	• IF ON SKIN: Wash with plenty of soap and water.
	• Do NOT induce vomiting.
	• In case of fire: Use suitable extinguishing media for extinction.
Storage	• The product must be stored in a cool, well-ventilated location where it will not be exposed
	to direct sunlight.
	Containers that have been opened must be tightly sealed.
	• Store in a well ventilated place. Keep cool.
	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
	• If there are any doubts about proper methods of handling the product, contact the point of
	purchase before proceeding with usage.